

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : B31D 5/00		A1	(11) International Publication Number: WO 95/28276
			(43) International Publication Date: 26 October 1995 (26.10.95)
(21) International Application Number: PCT/US95/04607		(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TT, UA, UG, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ, UG).	
(22) International Filing Date: 14 April 1995 (14.04.95)			
(30) Priority Data: 9400606 15 April 1994 (15.04.94) NL			
(71) Applicant (for all designated States except US): RANPAK CORP. [US/US]; 8023 Crile Road, Concord, OH 44077 (US).			
(72) Inventor; and (75) Inventor/Applicant (for US only): SIEKMANN, Dirk, Johannes [NL/NL]; Ophoven 65, NL-6133 XR Sittard (NL).			
(74) Agent: CAMPBELL, Jay, R.; Renner, Otto, Boisselle & Sklar, 19th floor, 1621 Euclid Avenue, Cleveland, OH 44115 (US).			
		Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	

(54) Title: A CUSHION PRODUCING MACHINE

(57) Abstract

A machine for manufacturing a cushioning product starting from a multi-ply stock (R) material or the like includes a frame (12) having a housing (14) with an exit opening, a stock supply supported by the frame, a forming assembly (28) causing the lateral edges of the stock material to roll inwardly to form a continuous strip (36) having lateral pillow-like portions and a central band, a gear assembly (34) for feeding the stock material through the forming assembly and out the exit opening, a cutting assembly (26) intermediate the gear assembly and the exit opening for cutting a determined length of the continuous strip to produce a cushioning product and, an access assembly (46) for permitting the cushioning product to be fed therethrough and inhibiting access to the cutting assembly from outside the housing.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

Title: A CUSHION PRODUCING MACHINE

### Field Of The Invention

5 This invention relates generally to a dunnage-creating machine such as a cushion producing machine for producing a dunnage product from sheet-like stock material supplied, for example, in roll form and, more particularly, to an assembly for such a machine which inhibits foreign objects from entering the cutting zone of the machine.

### Background Of The Invention

10 In the process of shipping an item from one location to another, a protective packaging material is typically placed in the shipping container to fill any voids and/or to cushion the item during the shipping process. Some commonly used protective packaging materials are plastic foam peanuts and plastic bubble pack. While these conventional plastic materials seem to perform adequately as cushioning products, they  
15 are not without disadvantages. Perhaps the most serious drawback of plastic bubble wrap and/or plastic foam peanuts is their effect on our environment. Quite simply, these plastic packaging materials are not biodegradable and thus they cannot avoid further multiplying our planet's already critical waste disposal problems. The non-biodegradability of these packaging materials has become increasingly important in light  
20 of many industries adopting more progressive policies in terms of environmental responsibility.

25 These and other disadvantages of conventional plastic packaging materials have made paper protective packaging material a very popular alternative. One machine which converts paper into a packaging material includes a stock supply assembly, a forming assembly, a gear assembly, and a cutting assembly, all of which are mounted on the machine's frame. During operation of such a cushion producing machine, the stock supply assembly supplies the stock material to the forming assembly. The forming assembly causes the lateral edges of the sheet-like stock material to roll inwardly to form a continuous strip having lateral pillow-like portions and a thin central band. The gear  
30 assembly pulls the stock material through the machine and also coins the central band of the continuous strip to form a coined strip. The coined strip travels downstream to the cutting assembly which cuts the coined strip into pads of a desired length.

For various reasons it is desirable to inhibit the entry of a foreign object into the cutting zone of the cutting assembly. In one known device a relatively long discharge path is arranged downstream of the cutting assembly so that so it is difficult for a foreign object to enter the cutting zone or to contact the cutting assembly.

### Summary Of The Invention

The present invention provides a cushion producing machine employing an access assembly downstream of the cutting assembly which is preferably open during the formation of a cushion and is closed prior to the initiation of a cutting process to inhibit access to the cutting assembly. Preferably, the machine is provided with a sensor which senses whether the access assembly is in an open or closed condition and which permits control of the cutting operation so that a cutting operation can only take place when the access assembly is in a closed condition. The access assembly may include a pair of flaps or valves, the positions of which are controllable so as to effectuate open and closed or semi-closed conditions or states for the access assembly. In accordance with the invention the access assembly is arranged in the exit opening of the machine and is controlled in time-dependent relation with the actuation of the cutting assembly. The access assembly can herein be arranged in close proximity to the cutting assembly so that the machine housing can be considerably reduced in size over machines which depend on a relatively long discharge path downstream of the cutting assembly to inhibit the entry of a foreign object into the cutting zone of the cutting assembly. In accordance with one aspect of the invention, a machine for manufacturing a cushioning product starting from a multi-ply stock material or the like includes a frame having a housing with an exit opening, a stock supply supported by the frame, a forming assembly causing the lateral edges of the stock material to roll inwardly to form a continuous strip having lateral pillow-like portions and a central band, a gear assembly for feeding the stock material through the forming assembly and out the exit opening, a cutting assembly intermediate the gear assembly and the exit opening for cutting a determined length of the continuous strip to produce a cushioning product and, an access assembly for permitting the cushioning product to be fed therethrough and inhibiting access to the cutting assembly from outside the housing.

In one preferred embodiment the access assembly includes at least one swivelling valve in the exit opening movable by a drive member.

According to a further embodiment, two swivelling valves are arranged in the exit opening for movement toward and away from each other, wherein the swivelling valves are moved synchronously by a joint coupling mechanism from the opened to the closed position.

These and other features of the invention are fully described and particularly pointed out in the claims. The following descriptive annexed drawings set forth in detail one illustrative embodiment, this embodiment being indicative of but one of the various ways in which the principles of the invention may be employed.

#### **Brief Description Of The Drawings**

In the annexed drawings:

Figure 1 shows a perspective standing view of an embodiment of the device according to the invention;

Figure 2 is a schematic view of the different components within the housing of the device; and

Figures 3 and 4 show in each case a perspective view of two embodiments of the access assembly according to the invention.

#### **Detailed Description Of The Invention**

With reference to the drawings and initially to Figure 1, there is shown a cushion producing machine 10 which includes a frame 12 with a housing 14 arranged thereon which comprises a number of processing assemblies discussed more fully below for converting sheet-like stock material into a cushioning product. It is noted that the illustrated embodiment of the frame 12 and the housing 14 is exemplary and that the frame and housing as well as other components of the machine 10 can be adapted to the particular place in which the machine will operate. In the illustrated embodiment the frame 12 is constructed from a number of profiles for support of the several components of the machine 10 including a rod 16 which supports a roll R of sheet-like stock material, such as Kraft paper. The paper 18 is unwound from the roll R and carried via reversing rollers 20 to the open underside of housing 14. The strip of paper 18 undergoes a

conversion operation in the housing 14 and is discharged through the exit opening 22 in the top of housing.

Figure 2 shows the different assemblies which cooperate to produce the cushioning product. In this figure the housing 14 of Figure 1 is omitted to reveal the assemblies within the housing. As can be seen the machine 10 further includes a conversion assembly 24 for converting the strip of paper 18 received from the roll R into a continuous strip of cushioning product and a cutting assembly 26 which cuts the continuous strip of cushioning product into cut pads of a desired length. The conversion assembly 24 includes a forming assembly 28 comprised of chute 30 with a forming frame 32 partially disposed therewithin, and a gear assembly 34 which coacts with the forming assembly to convert the sheet-like material into a continuous strip of cushioning product.

During the conversion process, the strip of paper 18 is fed through the forming assembly 28 wherein the lateral edges of the paper are caused to roll inwardly, such as in a spiralling fashion, to form a continuous strip 36 having lateral pillow-like portions and a thin central band. Through the forming process the thickness of the strip of paper is tripled. When triple-ply paper is used as the stock material, nine layers then lie on one another.

The gear assembly 34 includes a pair of enmeshed, toothed gears 38 forming a nip through which the strip of cushioning material 36 is fed and which coins the material as a result of the deformation by the teeth of the gears. It is also possible to use these toothed gears 38 to pull the strip of material upward in the direction of arrow P1. The gear assembly 34 is driven by the gear motor 40.

The cutting assembly 26 arranged above or downstream of the gear assembly 34 preferably includes a fixed blade 42 and a movable blade 43 which is driven by a cut motor 44.

Finally, an access assembly 46 in the form of two flaps, door or valves 48 is arranged above or downstream of cutting assembly 26, with the valves proximate the exit opening 22 of housing 14. The valves 48 serve to permit or to substantially close off access to the cutting zone of the cutting assembly 26 through the opening 22 depending upon whether the valves are in a relative open or closed position. The valves 48 have a trailing position relative to the transporting direction P1 and leave a determined opening between the distal edges thereof when in a closed condition such that the formed paper

strip 36 can be pulled out therebetween after being cut into a pad of a desired length by the cutting assembly 26. The position of the valves 48 is determined by a valve motor or similar motive means 50 and sensed by a sensor 52 which transmits a signal indicating the position of the valves to a control circuit, which is shown schematically by block 54 in Figure 2. The control circuit 54 also serves to control the gear motor 40, the cut motor 44 and the valve motor 50.

As shown in Figure 3, the access assembly 46 includes a front plate 56 and a parallel rear plate (not shown) which are mutually connected by spacer elements 58. The valves 48 swivel in the exit opening 22 on swivel shafts 60, 62 which have a parallel orientation. The swivel shafts 60, 62 are rotatably mounted in the plates with the end of the swivel shafts mounted in the front plate 56 protruding through the front plate in order to enable connection in each case to arms 64, 66, respectively. The other ends of the arms 64, 66 are mutually connected by an intermediate arm 68. Arranged on front plate 56 is the valve motor 50 which is connected pivotally to the arm 66 via a crank 70 and a crank arm 72. The valve motor 50 is energized and rotates in one direction so that the crank 70 turns, for instance, in the direction of arrow P3. This provides a reciprocating movement of crank arm 72 in the direction of arrow P4. The respective arms 64, 66 are thus caused to rotate about the axes of the swivel shafts 60, 62, respectively, thereby rotating the swivel shafts and causing the valves 48 mounted to the swivel shafts to be moved apart to a greater or lesser degree such that they are moved from a closed position, wherein the distal edges 74 of the valves lie substantially adjacent each other, to an open position, wherein the valves lie practically parallel to each other with their distal edges substantially separated.

Figure 4 shows an alternate embodiment of the drive mechanism for the access assembly 46. Arranged on front plate 56 is a solenoid 76 which serves as motive means for driving the arms 78, 80 connected to the swivel shafts 60, 62. The arms 78, 80 are embodied here as gear segments, the tothing of which is in engagement with a gear rack 82 which is joined to the solenoid pin 84. It will be apparent from Figure 4 that by energizing the solenoid 76 the pin 84 is pulled inwardly, carrying with it the gear rack 82, which rotates the two gear segments 78 and 80 and therewith the valves 48 of the access assembly 46.

In this embodiment the sensor 52 is embodied as microswitch, the arm 86 of which senses the position of the gear segment 78 via a roller 88 and thereby determines whether the valves 48 are in an open or closed condition. The sensor 52 generates a signal which is transmitted to the control circuit 54 in Figure 2 which, when the access assembly 46 is in its open position, renders inoperative the energizing of cut motor 44 of cutting assembly 26. The gear motor 40 powering the gear assembly 34 for through-feed of the strip of paper 36 can however be energized so that a determined strip can be discharged through the opening. Once the desired length of paper has been fed through the machine 10, the control circuit 54 commands the gear motor to stop and energizes the valve motor 50 or solenoid 76 to close the valves 48 of the access assembly 46. Once the sensor 52 has sensed that the valves 48 are in a closed condition and this information has been relayed to the control circuit 54, the control circuit energizes the cut motor 44 to cause the blades 42, 43 of the cutting assembly 26 to cut the strip of paper 36 to result in the appropriately sized length of cushioning product. Thereafter the user can pull the cut pad outward between the valves 48 to remove it from the machine for packaging a given item.

After the cutting operation is complete, e.g., the control circuit 54 has caused the blades 42, 43 to retract, the valve motor 50 can be energized to open the access assembly and the feed motor 40 can be started for renewed feed of the strip of paper 36 through the machine 10. It is noted that when closing of the valves 48 of the access assembly is prevented, for instance because of the presence of a foreign object between them, the control circuit 54 will not energize the cut motor 44 despite the possibility that the valve motor 50 for the access assembly has energized to close the valves. The interaction of the access assembly and the cutting assembly and gear assembly as controlled by the control circuit may be based on sensing of the states of the assemblies or based on a time dependant operation wherein the control circuit commands the respective assemblies to perform their operations based on a time sequence, or a combination of these control methods.

The invention is not limited to the above described embodiments. Many modifications of the invention given the preceding description will become apparent, all such modifications being within the scope of the invention. As an example, the sensor 52 may embodied as a different sensor or as multiple sensors, such as separate sensors



to determine if the access assembly is in an open position or a closed position. Moreover, opening or closing of the valves may be actuated by a variety of different actuation means. For example, the crank and linkage mechanism of Figure 3 could be combined with a pair of enmeshed partial gears such as illustrated in Figure 4, but  
5 without the intermediate gear rack, to effectuate control of the valves.

## CLAIMS

What is claimed is:

1. A machine for producing a cushioning product from a sheet-like stock material, comprising:

5 a frame having a housing with an exit opening;

a forming assembly, supported by the frame, which forms a continuous strip of dunnage from the sheet-like stock material;

a stock supply assembly, positioned upstream of the forming assembly, which supplies sheet-like stock material to the forming assembly;

10 a gear assembly, supported by the frame downstream of the stock supply assembly, for pulling the stock material from the stock supply assembly and advancing it through the forming assembly and out the exit opening;

a cutting assembly, positioned downstream of the exit opening, which cuts the continuous strip of dunnage to produce a cushioning product; and

15 an access assembly for permitting the cushioning product to be fed through the exit opening but inhibiting access to the cutting assembly through the exit opening.

2. A machine as set forth in claim 1 wherein the access assembly has an open position and a closed position, the machine including a sensor for determining which position the access assembly is in.

20 3. A machine as set forth in claim 2 including control means for controlling operation of the gear assembly and cutting assembly based on the position of the access assembly.

4. A machine as set forth in claim 3 wherein the access assembly is controlled in time-dependent relation with the actuation of the cutting means.

25 5. A machine as set forth in claim 1 wherein the access assembly includes at least one swivelling valve in the exit opening moved by a drive member.

6. A machine as set forth in claim 1 wherein the access assembly includes two swivelling valves arranged in the exit opening, and wherein a coupling mechanism moved by a drive member acts on the two valves.

30 7. A machine as set forth in claim 5 including a coupling mechanism formed by an arm which is connected to a swivel shaft, the free ends of which are coupled by an intermediate arm which engages a crank and crank arm driven by a motor.

8. A machine as set forth in claim 2 including a control circuit which prevents operation of the cutting assembly when the access assembly is not in its closed position.

9. A machine as set forth in claim 1 wherein the gear assembly performs a coining operation on the continuous strip.

5 10. A machine as set forth in claim 1 wherein the gear assembly includes a pair of enmeshed gears.

1/4







FIG. 1

FIG. 2



FIG. 4

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/US 95/04607

## A. CLASSIFICATION OF SUBJECT MATTER IPC 6 B31D5/00

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 B31D B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US,A,4 884 999 (BALDACCIO) 5 December 1989 ---	1
A	US,A,4 619 635 (OTTAVIANO) 28 October 1986 -----	1

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- \*&\* document member of the same patent family

Date of the actual completion of the international search

6 July 1995

Date of mailing of the international search report

22.08.95

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+ 31-70) 340-3016

Authorized officer

Peeters, S



# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 95/04607

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A-4884999	05-12-89	US-A- 5061543	29-10-91
		US-A- 5188581	23-02-93
US-A-4619635	28-10-86	CA-A- 1255376	06-06-89